

---

*North America's Leader in Hazardous Material Information Management*  
*1905 Aston Avenue, Carlsbad, CA 92008*  
*Phone (800) 451-8346 Fax (760) 602-8888*

---

## MSDS PRODUCT INFORMATION

Date: 10/07/2005  
To: MSDS Requester  
From: 3E Company  
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☒ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☐ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Behr Process Corporation  
Product Name: Build 50, Part A (DISCONTINUED)

BUILD 50 **M A T E R I A L   S A F E T Y   D A T A   S H E E T**  
**PART A**

Page: 1

PRODUCT NAME: BUILD 50 PART A  
PRODUCT CODE: 005199-10401

HMIS CODES: H F R P  
1 0 0 C

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: BEHR PROCESS CORPORATION  
ADDRESS : 3400 GARRY AVE.  
SANTA ANA, CA 92704

EMERGENCY PHONE : (800) 424-9300 DATE PRINTED : 04/28/00  
INFORMATION PHONE : (714) 545-7101 NAME OF PREPARER : Mike Butler

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE = 29.9 TDDP	WEIGHT PERCENT
Epoxy compounds	mixture		100.0

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.10  
VAPOR DENSITY: Heavier than air. EVAPORATION RATE: Slower than n-Butyl Acetate.  
COATING V.O.C.: 0 g/l MATERIAL V.O.C.: 0 g/l  
SOLUBILITY IN WATER: NIL.  
APPEARANCE AND ODOR:

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A METHOD USED: N/A  
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM CO2, DRY CHEMICAL

**SPECIAL FIREFIGHTING PROCEDURES**

Observe recommended procedures in handling fire areas. Wear appropriate fire fighting equipment including a self contained breathing apparatus. Avoid spreading of burning liquid with water used for cooling purposes.

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers are subject to bursting on exposure to heat. Liquid evaporates and forms invisible vapors which spread easily and can be ignited by many sources such as pilot lights, welding equipment, electrical switches. Fire hazard is greater as liquid temperature rises above 85 degrees F.

**FLAMMABILITY - T.D.G.R. CLASS**

DOT Not Regulated  
OSHA AND NFPA COMBUSTIBLE LIQUID CLASS IIIB

**SENSITIVITY TO IMPACT**

None known

**SENSITIVITY TO STATIC DISCHARGE**

None expected

## ===== SECTION V - REACTIVITY DATA =====

**STABILITY:** Stable.

**CONDITIONS TO AVOID**

Avoid heat flame and contact with strong oxidizing agents

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Product will soften or dissolve some plastics

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

Incomplete combustion can lead to the evolution of Carbon Dioxide and/or Carbon Monoxide

**HAZARDOUS POLYMERIZATION:** Will not occur

## ===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Product is a mild irritant Effects are temporary and reversible Vapor odors may cause irritation in the upper and lower respiratory tracts nausea, headaches and dizziness

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Product is a mild irritant to skin and eyes Effects are temporary and reversible Product may cause irritation redness and tearing

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Product is corrosive Do not allow this product to contact unprotected skin CALL PHYSICIAN IMMEDIATELY

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Harmful if swallowed Ingestion can cause nausea, vomiting diarrhea and gastrointestinal irritation

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute Health Hazards Repeated skin contact may result in the development of an allergic skin reaction in a small number of individuals

Chronic Health Hazards Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage

**CARCINOGENICITY:** NTP CARCINOGEN: Product is not a known carcinogen  
**IARC MONOGRAPHS:** NO  
**OSHA REGULATED:** NO

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Available toxicology, chemical and physical data show that overexposure is unlikely to aggravate any medical condition

**EMERGENCY AND FIRST AID PROCEDURES**

**EYE CONTACT** Flush with water for 15 minutes Expose to fresh air Call Physician immediately

**SKIN CONTACT** Wash with soap and water for 15 minutes

**INHALATION** Remove to fresh air Call physician if experiencing any difficulty breathing

**INGESTION** DO NOT INDUCE VOMITING! CALL PHYSICIAN IMMEDIATELY Activated charcoal may be administered If conscious feed two glasses of water

## ===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Dike and/or absorb spilled material with inert absorbent material such as sand or sawdust Use rags to clean up small amounts of spilled materials Remove all ignition sources Ventilate confined areas Keep people away

**WASTE DISPOSAL METHOD**

DISPOSAL DANGER - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep container closed when not in use. Do not store or handle near heat, flames or strong oxidants. Store in cool, well ventilated areas, rotate stock to use older material first. Inspect for leaks or cracks in all containers.

**OTHER PRECAUTIONS****===== SECTION VIII - CONTROL MEASURES =====****RESPIRATORY PROTECTION**

None normally needed

**VENTILATION**

General mechanical ventilation may be sufficient to keep product vapor concentrations below the specified TLV levels. If adequate one can also use local exhaust.

**PROTECTIVE GLOVES**

Use solvent impermeable Neoprene or latex gloves to protect against skin contact.

**EYE PROTECTION**

Use safety goggles, safety glasses and/or face shields to protect the eyes.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Impermeable aprons or protective clothing are recommended when working with this product. The use of head caps is also recommended whenever possible.

**WORK/HYGIENIC PRACTICES**

Care should be taken to prevent unnecessary exposure to this product. Eye washes and safety showers should be available.

**===== SECTION IX - DISCLAIMER =====**

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originated with the company or not. Since the use of this information and the conditions of use are not within the control of the manufacturer, it is the user's obligation to determine the conditions for safe use of this product.